

TECHNICAL DATA SHEET

Version: april 2017

SPEED WATER FOUNTAIN SOLUTION

CODE: C000000105

Wet universal additive for offset sheet printing without isopropyl alcohol.

TECHNICAL SPECIFICATIONS

- Colour
- pH VALOUR

4,8 – 5,2

BLUE

PROPERTIES

- Strongly reduces or eliminates the need isopropyl alcohol.
- Ensures a quick start for minimum paper waste.
- The new development prevents bacteriological contamination, is completely biodegradable and harmless to the user.
- Excellent print stability and colour, also suitable for high speed presses.
- It can be used with all types of water.
- Corrosion inhibitors, according to OEM standards.
- Suitable for conventional inks, UV or hybrid.

RECOMMENDATIONS

Dosage

- SPEED WATER FOUNTAIN SOLUTION dosage. Use a maximum of 3% to 4%.
- Dosing of isopropyl alcohol. Minimizing from 0% to 4%.

Improved results

- Important: make sure to use the correct dose of the reccomended concentration.
- Important: replace wet filters additive, at least once at week.
- We have additives for use with reverse osmosis water.
- We have additives to keep clean the water circuit wet.

PACKAGING

- 10 kg
- 25 kg
- 225 kg
- 1000 kg

Consult the safety data sheet for more information on handling, storage and personal protection. The information referred to here above is base don currently available data and no blinding guarantee regarding the suitable for certain uses and conditions of use is granted. Martínez Ayala reserves the rigth to modify the characteristics of the products, when necessary for technical reasons, environmental or production. Storage: 5-40 °C. Retention period: 12 months. Protect from direct sunlight.

The SPEED WATER FOUNTAIN SOLUTION has been developed by R&D Department of MARTINEZ AYALA, S.A.



MARTINEZ AYALA, S.A.

